

DATA SHEET

ETACRYL-NON-SLIDING-COAT

PRODUCT: 2 Components on acrylic-resin isocyanate basis with excellent adhesion on aluminium and galvanized steel.

ADDITIONS: ETACRYL-HARDENER 60 – 700
ETACRYL-THINNER 60 – 900

MIXING RATIO: 7 : 1 mit Härter 60 – 700

COLOUR: RAL 7012 grey

FIELD OF APPLICATION: For aluminium and galvanized steel structures for indoor and outdoor (e.g. gangways, stairways).

SURFACE PREPARATION: The surface must be dry and free from grease and dust.

APPLICATION: rolling

DRYING: to touch: after approx. 1 h / 20° C
dry through: after approx. 16 h / 20° C

POTLIFE: approx. 6 hours at 20° C

TEMPERATUR RESISTANCE: max. 80° C

STORAGE: Minimal shelf life 12 months (hardener 6 months) when stored indoors with a temperature between +5° C and +30° C and kept in original closed cans.

This product data sheet and the recommendation for usage it contains where based on data believed to be reliable and are intended or use by personal having skill and know-how at their own discretion and risk, in accordance with current industry practice and normal operating conditions. Variations in environment, changing in operating procedures or extrapolation of data may cause unsatisfactory results obtained from the use of this product or for any consequential or incidental effects of any kind.

Important note: for surface steel, after appropriate surface pretreatment, apply corrosion protection like ETAPOX Grundierfüller 71-200 or others.

These data are based on experience. As we have no influence on the processing, we are only able to guarantee the constant quality of our products. Subject to alterations.

Erscheinungsdatum date: 01/07/2023
Copyright © KANSAI HELIOS Austria GmbH